

AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions and listings of claims in the application.

LISTING OF CLAIMS

1. (Currently Amended) ~~[[A]]The motor drive for an electric machine,~~
~~comprising:of claim 10~~

~~a live line;~~

~~a second line;~~

~~a ground line; and~~

~~a surge protector including:~~

~~a first varistor; and~~

~~a gas discharge tube (GDT) that is non-conductive below a trigger voltage and that is conductive above said trigger voltage, wherein the trigger voltage is greater than a hi-pot test voltage;~~

~~wherein said first varistor and said GDT are connected in series between one of said live line and said second line and said second line and said ground line, said GDT being operably connected to clamp voltage in said surge protector by diverting excess voltage from one of said live line and said second line to said ground line.~~

2. (Currently Amended) The motor drive of claim ~~[[1]]10~~ wherein said first varistor has a voltage threshold that is less than a hi-pot test voltage and said trigger

voltage, wherein said hi-pot test voltage is less than said trigger voltage, and wherein said trigger voltage is less than a surge voltage.

3. (Currently Amended) The motor drive of claim ~~[[1]]~~10 wherein said surge protector further comprises a second varistor connected between the other of said live line and said second line and said second line and said ground line.

4. (Original) The motor drive of claim 3 wherein when a voltage on said live line exceeds said trigger voltage, said first varistor, said second varistor and said GDT clamp excess voltage between said live line and said second line and clamp excess voltage between said second line and said ground line.

5. (Currently Amended) The motor drive of claim ~~[[1]]~~10 wherein said surge protector further includes a fuse that is connected in series with said live line and that creates an open-circuit when current flowing through said fuse exceeds a current threshold of said fuse.

Claim 6 cancelled.

7. (Currently Amended) The motor drive of claim ~~[[6]]~~10 wherein said rectifier is a doubler-type rectifier.

8. (Currently Amended) The motor drive of claim ~~[[1]]~~10 wherein said second line is a neutral line.

9. (Currently Amended) The motor drive of claim ~~[[1]]~~10 wherein said second line is a second live line.

10. (Previously Presented) A motor drive for an electric machine, comprising:

- a live line;
- a second line;
- a ground line;
- a rectifier that communicates with said live line, said second line and said ground line and that converts an AC power input to a DC power output;
- a first capacitor that is coupled between a first output of said rectifier and said second line;
- a second capacitor that is coupled between a second output of said rectifier and said second line; and
- a surge protector including:
 - a first varistor; and
 - a gas discharge tube (GDT) that is non-conductive below a trigger voltage and that is conductive above said trigger voltage,

wherein said first varistor and said GDT are connected in series between one of said live line and said second line and said second line and said ground line.

11. (Original) The motor drive of claim 10 further comprising:

a first resistor that is connected in parallel to said first capacitor;

a second resistor that is connected in parallel to said second capacitor.

12. (Original) The motor drive of claim 3 wherein said first and second varistors are metal oxide varistors (MOVs).

13. (Currently Amended) ~~[[A]]The motor drive of claim 19 for an electric machine, comprising:~~

~~a live line;~~

~~a second line;~~

~~a ground line; and~~

~~a surge protector including:~~

~~a first varistor;~~

~~a gas discharge tube (GDT) that is non-conductive below a trigger voltage and that is conductive above said trigger voltage, wherein the trigger voltage is greater than a hi-pot test voltage, and said first varistor and said GDT are connected in series between one of said live line and said second line and said second line and said ground line, said GDT being operably connected to clamp voltage in said surge protector by diverting excess voltage from one of said live line and said second line to said ground line; and~~

~~a second varistor connected between the other of said live line and said second line and said second line and said ground line.~~

14. (Currently Amended) The motor drive of claim ~~[[13]]~~19 wherein said first and second varistors have a voltage threshold that is less than a hi-pot test voltage and said trigger voltage, wherein said hi-pot test voltage is less than said trigger voltage, and wherein said trigger voltage is less than a surge voltage.

15. (Currently Amended) The motor drive of claim ~~[[13]]~~19 wherein when a voltage on said live line exceeds said trigger voltage, said first varistor, said second varistor and said GDT clamps excess voltage between said live line and said second line and clamps excess voltage between said second line and said ground line.

16. (Currently Amended) The motor drive of claim ~~[[13]]~~19 wherein said surge protector further includes a fuse that is connected in series with said live line and that creates an open-circuit when current flowing through said fuse exceeds a current threshold of said fuse.

Claim 17 cancelled.

18. (Currently Amended) The motor drive of claim ~~[[17]]~~19 wherein said rectifier is a doubler-type rectifier.

19. (Previously Presented) A motor drive for an electric machine, comprising:
a live line;
a second line;

a ground line;

a rectifier that communicates with said live line, said second line and said ground line and that converts an AC power input to a DC power output;

a first capacitor that is coupled between a first output of said rectifier and said second line;

a second capacitor that is coupled between a second output of said rectifier and said second line; and

a surge protector including:

a first varistor;

a gas discharge tube (GDT) that is non-conductive below a trigger voltage and that is conductive above said trigger voltage, wherein said first varistor and said GDT are connected in series between one of said live line and said second line and said second line and said ground line; and

a second varistor connected between the other of said live line and said second line and said second line and said ground line.

20. (Currently Amended) The motor drive of claim 19 further comprising:

a first resistance having one end that is connected in parallel to said first capacitor;

a second resistance that is connected in parallel to said second capacitor.

21. (Currently Amended) The motor drive of claim ~~[[13]]~~19 wherein said first and second varistors are metal oxide varistors (MOVs).

22. (Currently Amended) The motor drive of claim ~~[[13]]~~19 wherein said second line is a neutral line.

23. (Currently Amended) The motor drive of claim ~~[[13]]~~19 wherein said second line is a second live line.

24. (Currently Amended) A method for insulation testing an electric machine with a surge protection circuit without using a jumper circuit to disconnect said surge protection circuit during said insulation testing, comprising:

providing an electric machine having a live line, a ground line and a second line;

converting an AC power input to a DC power output via a rectifier that communicates with said live line, said ground line and said second line;

providing a first capacitor between a first output of said rectifier and said second line;

providing a second capacitor between a second output of said rectifier and said second line;

connecting a first varistor and a gas discharge tube (GDT) in series between one of a live line and a second line and said second line and said ground line, thereby operably connecting said GDT to clamp voltage by diverting excess voltage from one of said live line and said second line to said ground line;

setting a trigger voltage of said GDT greater than a hi-pot test voltage, wherein said GDT is conductive above said trigger voltage and non-conductive below said trigger voltage; and

performing said insulating testing.

Claim 25 cancelled.

26. (Previously Presented) The method of claim 24 further comprising setting a voltage threshold of said first varistor less than a hi-pot test voltage and said trigger voltage, said hi-pot test voltage less than said trigger voltage, and said trigger voltage is less than a surge voltage.

27. (Original) The method of claim 26 wherein said surge protector further comprises a second varistor connected between the other of said live line and said second line and said second line and said ground line.

28. (Original) The method of claim 27 further comprising clamping excess voltage between said live line and said second line and between said second line and said ground line when a voltage on said live line exceeds said trigger voltage using said first varistor, said second varistor and said GDT.

29. (Currently Amended) The motor drive of claim ~~[[1]]~~10 wherein said hi-pot test voltage is equal to a twice a live line voltage plus 1000V.

30. (Previously Presented) The motor drive of claim 29 wherein said hi-pot test voltage is between greater than or equal to 1230V.

31. (Previously Presented) The motor drive of claim 29 wherein said hi-pot test voltage is less than or equal to 1460V.

32. (Previously Presented) The method of claim 24 wherein performing said insulating testing comprises applying a voltage signal to said live line.

33. (Previously Presented) The method of claim 32 wherein said applied voltage signal is applied for a test time.

34. (Previously Presented) The method of claim 34 wherein said test time is one second.

35. (Previously Presented) The method of claim 32 wherein said applied voltage signal includes a voltage greater than or equal to 1230V and less than or equal to 1800V.